

Welcome to the Sulfur *family*

**Now
Available**

Sulfur in Residual, Isooctane, Mineral Oil and Diesel Fuel Standards



Sulfur in Residual Oil

ppm	Residual Oil, 50mL	Residual Oil, 100mL
2,500	150-420-100	150-420-005
3,500	150-420-105	150-420-010
5,000	150-420-110	150-420-015
7,500	150-420-120	150-420-020
10,000	150-420-125	150-420-025
15,000	150-420-130	150-420-030
20,000	150-420-135	150-420-035
25,000	150-420-140	150-420-040
30,000	150-420-145	150-420-045
35,000	150-420-150	150-420-050
40,000	150-420-155	150-420-055
50,000	150-420-160	150-420-060

**Premier supplier of oil analysis standards
and supplies for the atomic spectroscopy market
with superior chemistry and excellent
customer service.**

Analysis of:

- Petroleum products
- Organic fluids/materials
- Lubricant additives

**Registered
ISO 9001:2008
Compliant**



USA

Tel.: (800) 361-6820
Fax: (800) 253-5549

Canada / International

Tel.: (800) 361-6820 / +1 (514) 457-0701
Fax: (800) 253-5549 / +1 (514) 457-4499

Europe

Tel.: +33 (0) 1 69 18 71 17
Fax: +33 (0) 1 60 92 05 67

MK-MKG003-SSTD-1.0-E

China

Tel.: +86 (10) 58032301
Fax: +86 (10) 58032302



Quality & stability is our *guarantee*

The quality of many petroleum products is related to the amount of sulfur present. In fuels, the amount of sulfur is related to its performance characteristics and vehicle emission levels. Levels of sulfur in petroleum and petroleum products are regulated through federal, state and local agencies.



Conostan offers a growing product line of sulfur standards and includes our new sulfur in residual oil and sulfur in isooctane standards. Custom concentrations are available.

Sulfur in Isooctane by UV Set of 7 x 10mL

Concentration ppm	Catalogue no.	Description
0, 0.5, 1.0, 2.5, 5.0, 7.5, 10	150-430-010	For very low Sulfur level, set of 7 x 10mL vials. Complete with a Certificate of Analysis.
0, 5.0, 10, 25, 50, 100, 250	150-430-020	For low Sulfur level, set of 7 x 10 mL vials. Complete with a Certificate of Analysis.
0, 50, 100, 250, 500, 750, 1000	150-430-030	For high Sulfur level, set of 7 x 10 mL vials. Complete with a Certificate of Analysis.

Sulfur in Isooctane

ppm	Isooctane, 60mL
0 (Blank)	150-430-101
50	150-430-102
100	150-430-103
250	150-430-104
500	150-430-105
750	150-430-106
1,000	150-430-107
Set of 7	150-430-100

Sulfur in Mineral Oil / Diesel Fuel #2

ppm	Mineral Oil, 100g	Diesel Fuel #2, 100g
0 (Blank)	150-400-025	150-410-012
50	150-400-018	150-410-009
100	150-400-002	150-410-002
250	150-400-010	*
500	150-400-019	150-410-010
750	150-400-023	150-410-018
1,000	150-400-003	150-410-003
2,500	150-400-011	*
5,000	150-400-020	150-410-011
7,500	150-400-024	150-410-021
10,000	150-400-004	150-410-004
15,000	150-400-005	150-410-006
20,000	150-400-008	150-410-007
25,000	150-400-012	*
30,000	150-400-014	150-410-022
40,000	150-400-016	150-410-023
50,000	150-400-021	150-410-024

Come visit us on the web at www.conostan.com or email us at sales@scpscience.com

USA

Tel.: (800) 361-6820
Fax: (800) 253-5549

Canada / International

Tel.: (800) 361-6820 / +1 (514) 457-0701
Fax: (800) 253-5549 / +1 (514) 457-4499

Europe

Tel.: +33 (0) 1 69 18 71 17
Fax: +33 (0) 1 60 92 05 67

China

Tel.: +86 (10) 58032301
Fax: +86 (10) 58032302